



TOWNSHIP OF HAMILTON
COUNTY OF MERCER
NEW JERSEY

DRIVEWAY/PARKING AREA PERMIT

Tax Map Page _____

NO. _____

Block _____ Lot _____

Date _____

Permission is hereby granted to _____

(Address) (Phone #)

- Remove & Replace Existing _____ ft. wide
- Construct New: _____ ft. wide * bituminous * concrete driveway/parking area
- Overlay Existing → 4" thick (min.) 5" thick 6" thick

by _____ Contractor License No. _____

Notes:

Fee \$ \$30.00 Cash Check

This permit is issued upon the condition and understanding that the permittee is responsible to ensure that the work is in strict accordance with the specifications listed below*. The contractor shall perform work necessary for total installation of the work covered by this permit. This includes quality control inspections necessary for conformity with the specifications. This permit becomes null & void unless exercised with one (1) year from date of issue.

Paid By _____

Samantha Brown
Township Engineer

Taken by _____

THE APPLICANT OR CONTRACTOR MUST SUBMIT A COPY OF A PLOT PLAN TO WIDEN A DRIVEWAY. DRIVEWAYS SHALL NOT CREATE DRAINAGE PROBLEMS ON ADJOINING PROPERTIES.

THE DEPARTMENT OF PUBLIC WORKS INSPECTOR MUST BE GIVEN 48 HOURS NOTICE. AN INSPECTION IS REQUIRED BEFORE ANY PAVEMENT IS PLACED. THIS INSPECTION IS TO ENSURE THAT THE DRIVEWAY GENERALLY CONFORMS TO THE DIMENSION AND LOCATION PRESCRIBED ON THIS PERMIT AND ON THE SITE PLAN. CALL (609) 586-0311 TO SCHEDULE AN INSPECTION.

DATE INSPECTED _____ INSPECTOR _____ APPROVED YES NO

IF NO, WHY _____

RE-INSPECTED _____ INSPECTOR _____ APPROVED YES NO

IF NO, WHY _____

**** IF OWNER TAKES OUT PERMIT, HE/SHE MUST SIGN THE FOLLOWING:**

I, _____, owner of the above property, will take full responsibility for the paving being done on my property. This responsibility includes necessary oversight for quality control and adherence to the specifications.

(Signature of Owner)

***SPECIFICATIONS**

1. Concrete mix must be 4000 psi and truck delivered from a concrete company that is NJ State certified.
2. Bituminous - 2" (compacted) top over 4" of stone or 4" recycled concrete
3. In front of the driveway you must have 6" thick concrete sidewalk and apron.
4. Driveway overlay must be tack coated and keyed (12" minimum) at both limits.

Sec. 160-119 (j)(4): "Driveways shall be no closer than 5 feet to any side or rear property line....not to exceed 20 feet in width."